



G-Snack XL Master

G-SNACK DESIGN

Snacking, Solved!

THE COMPLETE SOLUTION

An evolutionary snack machine presented with a new look.

A spacious and brightly illuminated showcase enhances the product display.

An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system.

New software features of shelf detection and secure vending system make the machine complete.

Slave versions are now available to operate with G-Caffè, G-Drink DESIGN as well as G-Snack DESIGN and extends further versatile utility.



**G-SNACK DESIGN
TWELVE (XII) MASTER
SDL**



**G-SNACK DESIGN
TEN (X) MASTER
SDX**



**G-SNACK DESIGN
EIGHT (VIII) MASTER
SC8**



**G-SNACK DESIGN
SIX (VI) MASTER
SC6**

DIMENSIONS H x W x D	1830* x 1290 x 900 mm			1830* x 1125 x 845 mm			1830* x 980 x 845 mm			1830* x 830 x 845 mm																										
WEIGHT (NET - Standard machine without options)	410 kg			340 kg			310 kg			275 kg																										
NO. OF SELECTIONS PER SHELF	12			10			8			6																										
NO. OF SHELVES	Max. 7			Standard 6 / Max. 7			Standard 6 / Max. 7			Standard 6 / Max. 7																										
NO. OF SELECTIONS	Max. 84			Max. 70			Max. 56			Max. 42																										
PROTOCOL	Executive / MDB			Executive / MDB			Executive / MDB			Executive / MDB																										
COOLING SYSTEM CONTROL	Electronic			Electronic			Electronic			Electronic																										
ECO-FRIENDLY COOLING UNIT AVAILABLE	-																																			
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C			+2°C up to +18°C			+2°C up to +18°C			+2°C up to +18°C																										
MAX. POWER CONSUMPTION	600 W			600 W			600 W			550 W																										
POWER SUPPLY	230 V / 50 Hz			230 V / 50 Hz			230 V / 50 Hz			230 V / 50 Hz																										
CLIMATE CLASS	ST (+16°C up to +38°C)			ST (+16°C up to +38°C)			ST (+16°C up to +38°C)			ST (+16°C up to +38°C)																										
ENERGY CLASS	 Cat. 2			 Cat. 3			 Cat. 4			 Cat. 2			 Cat. 3			 Cat. 4																				
ENERGY CONSUMPTION - kWh/annum	1811 Cat. 2			2329 Cat. 3			2455 Cat. 4			1969 Cat. 2			2253 Cat. 3			2293 Cat. 4			1704 Cat. 2			2133 Cat. 3			2114 Cat. 4			1877 Cat. 2			2213 Cat. 3			2716 Cat. 4		
ENERGY CLASS (HC-R290)	-			 Cat. 2			 Cat. 3			 Cat. 4			 Cat. 2			 Cat. 3			 Cat. 4			-			-			-								
ENERGY CONSUMPTION (HC-R290) kWh/annum	-			2524 Cat. 2			3019 Cat. 3			3150 Cat. 4			2337 Cat. 2			2787 Cat. 3			2589 Cat. 4			-			-			-			-					

* With adjustable feet. ** 25°C RT - 65% H

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment



OPTION LIST

Safety slide coin insert
Customization
HC R290 cooling unit
CO₂ cooling unit
Customized cabinet colour
Kit EVA DTS
Front glass protection
Motorized lock delivery eyelet
Security cash box system
Various fitting kits
Special cables
Special coded lock (Rielda)

Speedy lift
Touch screen
Validator kit
Kit sandwich/baguette
Wall/floor fixing kit
Roof kit
E-labeling

STANDARD COLOUR

Black ●



DUO SYNCHRO SPIRAL
An innovative system with a double motor drive that rotates perfectly synchronized in distance. Ideal for wide and bulky products.



SPEEDY LIFT
Delicate and/or fragile products can be sold at eye-height position! Speedy delivery of the products is guaranteed!