Your sleek vending ally

Just when you thought that your vending business couldn't get any better, SandenVendo launched the sophisticated G-Snack Design Slave automatic vending machine. Engineered to function with any G-Caffè, G-Drink and G-Snack master machine model that holds the selection panel and a single payment system, G-Snack Design Slave is the refined, hi-tech vending solution that will serve as a proper business ally to your existing vending installation: try pairing it with a G-Caffè vending machine and let your customer indulge in a treat to combine with an authentic Italian espresso.

SS8 / KS8

G-Snack Design Eight (VIII) Slave

TECHNICAL SPECIFICATIONS	SS8 / KS8
DIMENSIONS H x W x D (mm)	1830 x 830 x 845
WEIGHT (NET - Standard machine without options)	240 kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	681 (Cat. 2) 849 (Cat. 3) 878 (Cat. 4)

*With adjustable feet

OPTIONAL

- SPEEDY LIFT
- E-LABELING
- BELT SYSTEM
- ROTARY SYSTEM
- KIT SANDWICH
- KIT BAGUETTE
- MOTORIZED LOCK DELIVERY EYELET
- SPECIAL CODED LOCK (RIELDA)
- WALL/FLOOR FIXING KIT
- VARIOUS FITTING KITS
- CUSTOMIZATION
- CUSTOMIZED CABINET COLOUR

© SandenVendo GmbH
Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.

Your sleek vending ally

Just when you thought that your vending business couldn't get any better, SandenVendo launched the sophisticated G-Snack Design Slave automatic vending machine. Engineered to function with any G-Caffè, G-Drink and G-Snack master machine model that holds the selection panel and a single payment system, G-Snack Design Slave is the refined, hi-tech vending solution that will serve as a proper business ally to your existing vending installation: try pairing it with a G-Caffè vending machine and let your customer indulge in a treat to combine with an authentic Italian espresso.

SSX / KSX

G-Snack Design Ten (X) Slave

TECHNICAL SPECIFICATIONS	SSX / KSX
DIMENSIONS H x W x D (mm)	1830 x 980 x 845
WEIGHT (NET - Standard machine without options)	290 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	694 (Cat. 2) 869 (Cat. 3) 925 (Cat. 4)

*With adjustable feet

OPTIONAL

- SPEEDY LIFT
- E-LABELING
- BELT SYSTEM
- ROTARY SYSTEM
- KIT SANDWICH
- KIT BAGUETTE
- MOTORIZED LOCK DELIVERY EYELET
- SPECIAL CODED LOCK (RIELDA)
- WALL/FLOOR FIXING KIT
- VARIOUS FITTING KITS
- CUSTOMIZATION
- CUSTOMIZED CABINET COLOUR

© SandenVendo GmbH
Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.