



NarrowStack Basic 550-8 DD

Ready to serve 24 hours a day

THE SANDENVENDO COLD DRINKS VENDING MACHINES

- Easy programming using selection button sequence
- Electronic control and data-recording
- Energy Management by real time clock
- Each column driven via individual vend motor
- 24 V DC motors
- Interchangeable parts
- Quadruple loading for 0.33 l cans and double loading for 0.50 l PET bottles up to 245 mm height

DIMENSIONS H x W x D (mm)	1830 x 850 x 940
WEIGHT (NET - Standar machine without options)	335 Kg
NO. OF SELECTIONS / COLUMNS	8 / 8
MAX. CAPACITY (0.33 l CANS)	544
MAX. CAPACITY (0.50 l PET BOTTLES)	272
MAX. PRODUCT LENGTH (mm)	505
MAX. PRODUCT DIAMETER (mm)	72
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Thermostat
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	580 W
POWER SUPPLY	230 V / 50 Hz



OPTION LIST

- CUSTOMIZED CABINET & DOOR COLOUR
- 2 LINE LCD DISPLAY
- SECURITY CASH BOX SYSTEM
- SAFETY SLIDE COIN INSERT
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- BRANDING
- OUTDOOR KIT IP34
- STACK ASSEMBLY FOR PRODUCT Ø 74 mm
- LOADING RACK

STANDARD CABINET COLOURS



Black